



## Product Identification

71208040

- Expert Smart Silent Cistern

## Definition and Application

- Preassembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall
- Compatible with all wall-hung WC pans
- Top or front activation/access

## Technical Features

### Structure

- Metal with 820mm, with 1,5mm thickness and corrosion resistant
- Easy and quick installation with Fast Fit system
- Minimum thickness of 150mm and adjustable up to 200mm
- Height regulation of the adjustable floor brackets (0-200 mm);
- Depth adjustable outlet bend
- Tested for 400kg load

## Technical Sheet

Expert Smart Silent Cistern For WM Toilet

### Cistern

- Dual flush in wall cistern compatible with either dual or single flush actuators 6/3 liters (adjustable to 4/2 or 7/3 liters)
- Mechanic actuation
- 150mm thickness
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene cistern highly resistable and inalterable to thermal stress
- Lower/under bench installation possibility
- Other versions compliant with: WRAS/SAI-WATERMARK/NF/BELGAQUA standards
- EN 14055 marking CL1
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

### Accessories

- 1 Discharge pipe ø 90 x 250
- 1 Seal for discharge pipe ø 125
- 1 Connecting pipe ø 45 x 180
- 1 Pan rubber seal ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend ø 90 / 90 L230
- 1 Protection pipe Ø90
- 1 Protection pipe Ø45
- 1 Adaptor pipe ø 90/110

#### Fixing accessories for wall structure:

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure
- 2 Fast Fit fixing

#### Fixing accessories for hung wc mounting on the structure

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Washers for WC pan fixation
- 2 Nuts M12
- 2 Washers ø 34

## Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid